

F1305-902 Safety Boot

S7S - BOA® Fit System - waterproof

MASCOT® FOOTWEAR INDUSTRY



09

| | | | | | | |
|------|------|------|------|------|------|------|
| 1140 | 1141 | 1142 | 1143 | 1144 | 1145 | 1146 |
| 1147 | 1148 | | | | | |

Main material/upper material

Full grain

Size 42: 769 g

| | | | | | |
|------------------------------|--------------------------|---|-----------------------------|--|---|
| E Shock-absorbing | A Antistatic | PS Nail nail protection (G-3mm) | WR Waterproof | FO Oil and fuel resistant sole | HRO Heat-resistant outsole compound |
| CI Cold insulation | LG Ladder grip | SC Scuff cap abrasion | SR Slip resistant | | |

MASCOTEX® MASCOLAYER®

Certifications



- Safety Class S7S
- Oil and fuel resistant sole (FO)
- Heat-resistant outsole compound (HRO)
- Cold insulation (CI)
- Ladder grip (LG)
- Scuff cap abrasion (SC)
- Slip resistant (SR)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022

Technical info

Opens and fastens with BOA® Fit System, which consists of a rotational dial, lace and guides. Composite toe cap. MASCOLAYER® textile nail protection. Moulded TPU scuff cap. Stabilising multi-functional shank with integrated absorbing cushioning. Midsole of PU. Rubber outsole with rubber friction inserts. Removable insoles, anti-static and durable. Shock absorbing insole. Absorbs and removes moisture. Sole is oil and petrol resistant. Heat resistant sole up to 300°C contact heat. Ladder grip. Waterproof membrane of MASCOTEX®. Water-repellent and breathable outer fabric. Suitable for working on the knees. Get a stable grip on all types of surfaces with the boot's slip-safe and self-cleaning outer sole. Non-marking sole - no scuff marks.

User

