

NLG Phone Harness™

Product Code:
101600

Max Load:
0.5 KG / 1.1 LBS




OVERVIEW

The NLG Phone Harness™ is the ultimate non-obstructive solution to secure your mobile phone at height. Fitting most smartphones, the unique design means the silicone tightens around the corners of the phone when dropped to ensure it stays securely in place.


VIEW ONLINE

<https://neverletgo.com/products/phone-harness/>



NLG ID™
Serialised and safe

Simply scan the NLG ID tag with your phone to instantly access certificates, instruction videos and log inspections. (See Specification if included).



Third-party tested and certified

Independent laboratory load testing certificates and Declarations of Conformity are available on request. Please contact team@neverletgo.com.

DESCRIPTION

The NLG Phone Harness™ is the simplest but most advanced phone holder for working at height. Patented features ensure the Holder provides unrivalled protection without compromising any functionality of the device itself.

The unique Rivertext core ensures stability and the self-tightening feature of the design ensures consistent performance in the harshest environments. Combining this with the selective use of specialist silicones guarantees a grip that increases as the weight and drop distance increase.

The Holder fits most commonly used phones without compromising the key functions of the device such as the camera, fingerprint recognition etc. When combined with the Mini Coil Lanyard (101371) it creates a simple easy-to-use tethering solution to keep one of the most commonly dropped (and most expensive) items secure when working at height, the mobile phone.

FEATURES

Fits phones ranging from sizes 130x60mm up to 200x110mm
 Durable welded Rivertext and silicone construction
 Unique design causes the harness to tighten around the phone if dropped
 Central attachment point eliminates "catapult effect" found on untested alternatives on the market
 Device functionality uncompromised - camera, ID recognition inc fingerprint etc.

TECHNICAL SPECIFICATION

Max Load: 0.5 KG / 1.1 LBS
 Safety Standards: ANSI/ISEA 121-2018, CE / UKCA, NS 9611:2022+AC
 Load Tested and Third-party Certified: Dynamic (2:1 Safety Factor)

Dimensions: 115mm (L) x 60mm (W)
 Max Lanyard Length: 120 CM / 48 IN

RETAIL

EAN (GTIN-13)
 5060572181038

UNIT WEIGHT (G)
 10

SHIPPING

HS CODE
 3926.90.1000

COUNTRY OF ORIGIN
 UK



Phone Harness™
Product Code: 101600

View online

<https://neverletgo.com/products/phone-harness/>

Learn more about:

[Dropped object prevention](#)

[Tool tethering](#)

[Tool lanyards](#)

Useful resources:

[Tool Box](#)

[Tool Tether Guide](#)

[Library](#)

CONTACT

+44 (0)330 016 0030

neverletgo.com

INSPECTION

In addition to routine checks before each use, all equipment should undergo regular detailed inspections, conducted and recorded by a competent person using the NLG Inspection Checklist. If any part is worn or shows signs of degradation, immediately retire from service. In the event of a drop, quarantine the equipment for a thorough inspection.

[Click to download Inspection Checklist](#)

LEGAL

NLG makes every effort to ensure the information in this Datasheet is accurate and current. However, NLG reserves the right to change the product specification when necessary. NLG cannot be held responsible for any inaccuracies or omissions.

Copyright © 2023. NLG® and Never Let Go® are registered trademarks.
