

DATASHEET

NANOLINK Y



GENERAL

Art.Nr:	L-0964-FS64-100	Standards:	ANSI Z359.13-2013, EN 355:2002,RFU PPE-R/11.063
GTIN:	4030281319061	Net weight:	1.83 kg
E-class number:	40-21-08-10	Gross weight:	1.98 kg
Customs tariff number:	56090000		

DATASHEET

NANOLINK Y

The NANOLINK Lanyard Series sets a new benchmark in fall protection and has been developed for demanding use across all industries. Its compact, ergonomic energy absorber reliably protects users from 50 to 150 kg, closing a critical safety gap that many conventional lanyards leave open. Highly abrasion-resistant materials ensure long-lasting durability even in harsh environments. Multiple variants with different connector options according to EN 362 allow flexible adaptation to individual requirements. NANOLINK combines freedom of movement, robustness, and uncompromising safety – for professionals who rely on their equipment at every height.

FEATURES

Colour:	Orange, Black
---------	---------------

Fallindicator:	Yes
----------------	-----

Impact force:	6.00 kN
---------------	---------

Hand wash:	30 °C
------------	-------

Edge approved:	No
----------------	----

Maximum lifetime:	10 years
-------------------	----------

Minimum tensile strength:	22.00 kN
---------------------------	----------

Min. temperature:	-35 °C
-------------------	--------

Max. temperature:	65 °C
-------------------	-------

Rescue loop:	No
--------------	----

Connector:	FS64 ALU
------------	----------

DIMENSIONS

length_lanyard:	1.00 m
-----------------	--------

Lanyard rope diameter:	11.00 mm
------------------------	----------

MATERIAL

Material:	Polyamide, Aluminium, Steel, Aramid, Various
-----------	--